


- [A] Impulsión de aire / Soufflage d'air / Air supply
 - [B] Retorno (MS423) o aire nuevo (MS324) / Reprise (MS423) ou air neuf (MS324) / Return (MS423) or fresh air (MS324)
 - [C] Retorno (MS324) o aire nuevo (MS423) / Reprise (MS324) ou air neuf (MS423) / Return (MS324) or fresh air (MS423)
 - ① Línea de líquido circuito 1 / Ligne de liquide circuit 1 / Liquid line of circuit 1
 - ② Línea de gas circuito 1 / Ligne de gaz circuit 1 / Gas line of circuit 1
 - ③ Línea de líquido circuito 2 / Ligne de liquide circuit 2 / Liquid line of circuit 2
 - ④ Línea de gas circuito 2 / Ligne de gaz circuit 2 / Gas line of circuit 2
 - ⑤ Evacuación condensados, c. int 3/4"M / Évacuation condensats, c. int. 3/4"M / Condensate drain, ind. c. 3/4"M
 - [6] Entrada agua bateria apoyo (opcional) / Entrée d'eau batterie d'appoint (en option) / Water inlet of hot water coil (optional)
 - [7] Salida agua bateria apoyo (opcional) / Sortie d'eau batterie d'appoint (en option) / Water outlet of hot water coil (optional)
 - [E] Acometida eléctrica / Alimentation électrique / Power supply
 - [F] Circulación aire interior / Circulation d'air intérieur / Internal air flow
- Perfil embocaduras: 20 mm / Profil embouchures: 20 mm / Profile outlets: 20 mm
Dimensiones en mm / Dimensions en millimètres / Dimensions in millimeters

Drawn by: C. Polonio	Revised by:	Approved by: R. Tubío	Date: 10/10/2018	Last modification: 10/10/2018	Scale: 1/50
		ISPK (indoor_module) - 240 MS-423-324 (plug-fan)			
		File name: ISPK(indoor_module)_240_ MS_423_324(plugfan).dwg	Technical brochure version: N.18 688 A	Version: 0	Page: 1/1